

Polycom® VSX™ 7000e

Features and Benefits



Audio

Siren™ 14 Wideband Audio	<ul style="list-style-type: none">• 14 kHz crystal clear audio• Eliminates fatigue associated with straining to hear every word• CD-quality sound for dynamic audio performance• Superb clarity to hear the subtleties of every word• Included on every system
Polycom StereoSurround™	<ul style="list-style-type: none">• 2 channels of 14 kHz crystal clear audio• Wideband audio projected in stereo, from left and right speakers• Superb clarity to hear the subtleties of every word• Easily decipher multiple, simultaneous conversations• Distinguish which side of the room people are talking from, just like in a real meeting• Enable easily in the user interface and by attaching speakers to the VSX 7000e
SoundStation VTX 1000® Integration	<ul style="list-style-type: none">• Use the SoundStation VTX 1000 as the microphone for the video system and eliminate the VSX 7000e microphones• Add audio calls to a video conference with the SoundStation VTX 1000• Maximize the value of audio and video equipment investments when used together• Remarkable voice pickup range with the SoundStation VTX 1000 microphones• Video dial, mute, call hangup and call redial from the SoundStation VTX 1000 keypad
Enhanced Microphone Array	<ul style="list-style-type: none">• 360° audio pickup• Flotation feet filter out table-top noise• Sensitive enough to pick up whispers, smart enough to eliminate unwanted background noise• Versatile and attractive design for table top, wall or ceiling mount• Single array for Polycom StereoSurround• Gated enhanced stereo pickup
Audio Error Concealment	<ul style="list-style-type: none">• Reduced audio drop-out on busy IP networks• Smooth, consistent verbal communications without interruptions• Corrects audio from any system seamlessly• Activates automatically, only when needed
Direct POTS Connection	<ul style="list-style-type: none">• Easily add a caller (cell phone or landline) to any video call• Users on a cell phone can call directly into the video conference• Expands the usability of the system to include IP, ISDN, SIP or POTS callers

Video

Single Monitor XGA Support	<ul style="list-style-type: none">• Use a VGA display, or a TV for main display• Supports resolutions up to 1024 x 768• No need for a dual monitor system to clearly see content• Flexibility in configuration, allowing users to use the display of their choice
H.264 video up to 768Kbps	<ul style="list-style-type: none">• Use less bandwidth to conduct video calls• Unparalleled video quality for lower line rate applications• More bandwidth is available for other business• Cost savings to any organization!
Pro-Motion™ H.263 Video	<ul style="list-style-type: none">• Full-screen, TV-Like video quality• Greater image detail with 50/60 fields per second• Full screen maximizes display area• Fluid, precise motion handling• Most natural video communications experience possible



Polycom VSX 7000e Features and Benefits

Support for 16:9 or 4:3 Format	<ul style="list-style-type: none">• User selectable display format• 16:9 aspect ratio and Dual Monitor Emulation perfect for plasma displays• Accommodates regular TV monitors• High resolution graphics displays for Content presentation
Video Error Concealment	<ul style="list-style-type: none">• Reduced video drop-out on busy IP networks• Smooth, continuous video without interruptions• Maintain active face-to-face contact• Accomplish meeting objectives without worrying about the video integrity• Activates automatically, only when needed

Content Sharing

Direct XGA for Data Sharing	<ul style="list-style-type: none">• Based on H.239 standard, so it's possible to share data with other systems and vendors• See the presentation and the speaker at the same time• Perfect for outside speakers/visitors to be able to easily add content to a video conference; just plug in a PC directly to the 7000e and start sharing!• Or ImageShare II for easy table top connection and control
People+Content IP	<ul style="list-style-type: none">• Users can share data during a video conference without having to connect their PC to the system. Simply input the IP address into a small utility and PC content is automatically shown to all conference participants• This feature can be used by anyone in the conference, even audio callers!• An excellent option for wireless laptop users who are participating in a video conference
Multiple Content Sources	<ul style="list-style-type: none">• Doc camera and VCR images can be seen as content, along with people• Doc camera and VCR images do NOT displace the person talking, but show up next to them• Supplement video conference with multiple types of content including pictures, movies, audio files, PowerPoint® presentations• Flexible bandwidth settings for adjusting people and content
Adjustable Bandwidth for Content	<ul style="list-style-type: none">• Choose the amount of bandwidth to dedicate to content and people• Options include 90% Content/ 10% People; 50% Content/ 50% People; 10% Content/ 90% People• Adjustable setting located on the on-screen interface that can be accessed both during a call and outside of a call
Dedicated VCR/DVD ports for record/playback	<ul style="list-style-type: none">• Ability to use line level inputs for other devices• Easily play VCR/DVD movies/images during a video conference• Adds another dimension to the conference, making it like "being there"• See both the speaker and the DVD/VCR image

User Interface

Calendar & Call Scheduler	<ul style="list-style-type: none">• Quick and easy access to a monthly calendar with current date and time posting• Schedule repeat meetings to dial automatically• Create and save multipoint team meetings
Customizable Home Page	<ul style="list-style-type: none">• Display only the necessary buttons• Unique design to meet your organization's needs• Simplified graphical interface for novice users• Decreases learning curve• Leads to increased use of video
Peripheral Control Using RS-232 port	<ul style="list-style-type: none">• Use APIs to customize control of the system• Use an AMX® or Creston® panel as main UI• Brings flexibility for integrators to build a custom solution for their customers• Allows partners to add value to video conferencing solution• 2 ports available
Dual Monitor Emulation	<ul style="list-style-type: none">• Most efficient use of a single display area• Full size near and far video windows at the same time• Minimal investment, maximum benefit (one monitor, two screens)• Alternate layout views
User Selectable Camera Icons	<ul style="list-style-type: none">• Use icons that represent your industry• Intuitive icons match the input device• Custom name gives the icon clear meaning• Selection – 5 libraries to choose from• Decreases learning curve

Polycom VSX 7000e Features and Benefits

Kiosk Mode for Custom Applications	<ul style="list-style-type: none">• Makes video approachable and easy!• Create a look and feel that suits your application• Removes difficult decisions for the user• One-click dialing results in instant communications
Display Configuration Choices	<ul style="list-style-type: none">• Allows you to configure displays for your application• Single or dual displays• XGA or NTSC / PAL• 4x3 or 16x9 formats• Decide what shows on each display, near end, far end, or content
Platform Versatility	
Integration with Microsoft® Live Communications Server (LCS) via SIP	<ul style="list-style-type: none">• Integrates directly with Microsoft collaboration infrastructure• Registers and authenticates with Microsoft LCS 2005• VSX users can be added to Microsoft Messenger's buddy list• Presence information sent to LCS indicating video buddies' availability• Convenient dialing to email addresses
Supports up to (3) Microphone Arrays	<ul style="list-style-type: none">• Maximum coverage for extended rooms• Polycom StereoSurround support makes installing stereo even easier• Great audio pickup from every corner of the room• Each participant is near a microphone• Pin-point accuracy on the active speaker with multiple microphone arrays• Ceiling microphone can be seamlessly incorporated; provides coverage up to 40ft in diameter
Optional Network Interface Modules	<ul style="list-style-type: none">• Flexibility for any network type• Ability to upgrade as networks transition• Choose only the configuration you need• Easy to swap out• Modular, compact and out-of-the-way!
Internal Multipoint Software	<ul style="list-style-type: none">• Conduct meetings beyond just (2) sites• Increase productivity by including key people on the call• Adding sites during a call can lead to quicker decision making• Supports up to 4 video calls in one conference• Quick, easy upgrade with a software key
Advanced Encryption Standard	<ul style="list-style-type: none">• Communications are confidential and secure• Authentication by the National Institutes of Standards means it's credible• Built-in, no extra hardware required• Easy installation software key
Multiple Use RS-232 Ports	<ul style="list-style-type: none">• Multiple use RS-232 ports• 2 RS-232, DB9 ports• Camera control, Polycom or others• Transparent data pass-thru in H.320 or H.323• Control System connection• Vortex® audio system control• Peripheral options from Polycom Custom Products
E-Mail dialing format when dialing across IP security boundaries	<ul style="list-style-type: none">• Easy and intuitive E-mail video dialing• Operates with Polycom's V2IU™ Firewall Traversal Appliance• Deployable to wide range of between customers, suppliers and partners
Interoperability	
Part of the Polycom Office™	<ul style="list-style-type: none">• Remote management through Global Management System™• Extended conferencing with Polycom PathNavigator™• Expand the audience over audio and video with an MGC™ bridge• Consistency from a single manufacturer
Standards Based	<ul style="list-style-type: none">• Solid, reliable platform• Qualified by independent test labs• Interoperates with other vendors' systems that are standards-based• Install even in a mixed environment
Baseline Mode	<ul style="list-style-type: none">• Set your system to baseline mode, H.261 and G.711 for maximum interoperability with legacy video conferencing systems• Accessible via the web interface for easy access by the network administrator• Can be turned on and off as needed



Polycom Headquarters:

4750 Willow Road, Pleasanton, CA 94588 (T) 1.800.POLYCOM (765.9266) for North America only.
For North America, Latin America and Caribbean (T) +1.925.924.6000, (F) +1.925.924.6100

Polycom EMEA:

270 Bath Road, Slough, Berkshire SL1 4DX, (T) +44 (0)1753 723000, (F) +44 (0)1753 723010

Polycom Asia Pacific:

Polycom Hong Kong Ltd., Rm 1101 MassMutual Tower, 38 Gloucester Road, Wanchai, Hong Kong, (T) +852.2861.3113, (F)+852.2866.8028

Rev. 6/05

© 2005 Polycom, Inc. All rights reserved.
Polycom, the Polycom logo, Vortex and SoundStation VTX 1000 are registered trademarks and VSX, StereoSurround, Siren, People+Content, Pro-Motion, MGC, PathNavigator, Global Management System, ImageShare, PowerCam and The Polycom Office are trademarks of Polycom, Inc. in the U.S. and various countries.
All other trademarks are the property of their respective companies. Specifications are subject to change without notice.